## Narrow Row Crop Sprayer

## 100SR

## Supercharged

- 16-20 MaxCharge™ electrostatic nozzles
- 42 in. (106.68 cm.) in width; 800 lbs. (363 kg.) dry weight
- 56-150 gallon (212 -568 liter) poly tank
- Flow rate of 0.51-0.95 gal/min (1.92-3.6L/min.) (Example: 4mph at 10 ft centers equals an application rate of 9-17 gal/acre (84-159 liters/hectare)
- Supercharged blower means the spray goes higher and further
- Efficient and effective ultra low volume sprayer (40 micron droplet size) with minimum drift
- Easy 3-point hitch mounting; PTO powered
- "Category 2/3" lift class; 35 horsepower (26.1kW) tractor minimum required
- Control box with valve control and easyto-see electrostatic charge indicators
- Compatible with most conventional chemicals and fungicides
- Adjustable spray bars



Electrostatic Spraying Systems manufactures sprayers utilizing its patented MaxCharge™ technology. For more details please visit our website, www.maxcharge.com, or contact a representative at (706)769-0025.





Call today for the best possible deal on a 100SR sprayer for your operation.



## Electrostatic Means Better Spray Coverage



Electrostatic Spraying Systems 62 Morrison St. · Watkinsville, GA 30677-2749 Toll-Free: 800-213-0518 · Fax: 706-769-8072 www.maxcharge.com